

「銀河」運用記録 "GINGA" Daily Report

Ver. 1.71

199 0 MONTH : 6 DAY : 16 Y+ 1227

Written by :

F. Nagase

OPERATION: MNV from GX301-2 to G292.0+1.8 / HV Nominal

K. Terada

	[PASS 1]	[PASS 2]	[PASS 3]	[PASS 4]	[PASS 5]
NO.	900616-0309	900616-0412	900616-0516	900616-0619	900616-0722
AOS LOS	4:11:08 4:23:47	5:51:39 6:4:28	7:31:50 7:45:07	9:12:30 9:25:59	10:53:15 11:05:21
FLMX	20.16 17:09	58.48 57:20	天頂通過	63.81 18:26	23.33 58:37
COM MANDS	HV NOMINAL [C0.99] [C1.99] [C2.99] [C3.84]	SA 変調度測定 ・ 5/400 英 RX freq を 400 MHz に設定 ビデオ出力レベル調整 ・ ビデオ出力を 400 用 DEMO に入力して DEMO 復調テスト ・ 5/400 RX の IF (10 MHz) をスワップして スペクトラムを記録 (R)	IRU-Z Drift Cor [0D, E660] LAC-7 Top Fine Gain Adj. [D7 B6]	DUMMY PARA SET MNV STRT TRIM PARA SET [05, 79BF24000B] MNV STRT	DUMMY PARA SET MNV STRT SLEW PARA SET [05, 00007F0012] (0.5°/0.04 min)
TLMS	Repro		Repro	Repro	Repro
ACS	→ MNV →	Norm		MNV	
EVENT	6/16 0:01 (289.83) (97.26) (243.16) S360 前		6/16 6:23 (274.99) (98.61) (239.77) MNV 後		6/16 9:33 (275.13) (98.61) (239.85) Trim 後
S	4:20:00	06:00:00	7:41:00	9:22:00	11:02:01
PC PLAN	OG-5 4:22 BIT-MED 4:24 TMS-ON 4:26 LHV-RED 4:58 OG-5 5:34 OG-3 5:50	OG-5 6:03 BIT-MED 6:05 TMS-ON 6:07 OG-4 6:19 OG-5 6:29 LHV-RED 6:37 OG-5 7:09 OG-1 7:29 OG-3 7:31	OG-5 7:43 BIT-MED 7:45 TMS-ON 7:47 OG-4 7:55 OG-5 8:05 LHV-RED 8:19 OG-5 8:47 OG-1 9:09 OG-3 9:11	OG-5 9:24 BIT-MED 9:26 TMS-ON 9:28 OG-4 9:30 OG-5 9:40 LHV-RED 9:58 OG-5 10:26 OG-1 10:50 OG-3 10:52	OG-5 EXE 11:04 BIT LOW 11:06 TMS ON 11:08 OG-4 EXE 11:10 OG-6 EXE 11:20 BIT LOW 11:22 OG-5 EXE 11:36 OG-4 EXE 11:50 OG-5 EXE 16:00 OG-5 EXE 16:02 BIT LOW 22:10 OG-4 EXE 22:20 OG-4 EXE 09:20 OG-6 EXE 09:30 BIT LOW 09:32 OG-5 EXE 10:06 SLEW (-) 10:08 OG-6 EXE 11:20 OG-5 EXE 11:44 OG-6 EXE 13:02 OG-5 EXE 13:16 SLEW (+) 14:40 SLEW (+) 14:42 OG-4 EXE 18:48 OG-6 EXE 18:58 OG-7 EXE 20:00 SLEW 360 20:02 OG-4 EXE 20:24 OG-3 EXE 20:34 OG-1 EXE 20:36
COMMENT	④ この結果は工場に送って解析する。運用はビデオ出力レベルを個々の衛星(ぎんが、あけぼの)に合うようその都度調整すること。特に問題なし。] [LAC HV all on 今のところは問題なし。 ・ GX301-2 : Phase average spectrum; 20-40 keV 顕著な構造なし、20-40 keV は BGD 差引を注意深く行ってみる必要有、Phase 分けは?				
SANGLE	149.6-162.0	STT Y TEMP (MAX) 15.6 °C	MIN. -BAT-V (EOD) A 18.9 V (A 18.3 V)		