

「銀河」運用記録 "GINGA" Daily Report

Ver 1.71

199 0 MONTH : 6 DAY : 20 Y+ 1231

Written by :

Y. Tawara
K. Terada
CSR Day

OPERATION:

SN1987A PC

	[PASS 1]	[PASS 2]	[PASS 3]	[PASS 4]	[PASS 5]
NO.	900620-0207	900620-0310	900620-0413	900620-0517	900620-0620
AOS	2:59:01	4:39:20	6:19:50	8:00:26	9:42:29
LOS	3:11:30	4:51:58	6:33:05	8:13:17	9:52:25
ELMX	32.50 4:44	78.10 45:05	84.78 25:38	42.62 6:04	13.27 46:15
COMMANDS	SH REP DUMMY MNV Slew(+) セット 129.54°/9.64" [05,00,00,7F,12,12] PC mode ENA-φ[01,C2] PC OG-1	ST TRK LC E1 ON LC E2 ON DriftZ .CORR. [0D,E5,F3] -5.17°/R. DUMMY MNV SLEW 11° セット 5.99°/0.45 m [05,00,00,7F,00,D6] OG-1 PC	SH REP ST TRK LC E1 ON LC E2 ON PC OG-2 [SN1987A 304.98 105.91 283.70]	SH REP DUMMY MNV TRIM MNV TO SN1987A [05,DA,81,1D,00,1B] PC OG-2	SH REP MPC1 mode ENA-φ[01,02] PC-AD=50 ENA-B[00,32] PC CNT1
TLMS	Rep.(空)	Rangung	Rep.(空)	Rep.(空)	Rep.
ACS	Slew 11° セット	Slew 11° セット		Trim. MNV	
EVENT	5-360 前 6/19 23:07 296.68 104.66 154.00	5-360 後 6/20 0:41 296.63 104.68 152.46	Slew(+) 後 6/20 5:23 304.16 105.86 289.30		
ST	3:09:00	4:49:00	6:30:00	8:10:58	9:49:00
PLAN	TMS ON 3:11 LMV RED 3:13 BIT LOW 3:19 OG-5 3:21 SLEW(+) 3:23 BIT HI 3:33 OG-4 3:45 OG-6 3:57 OG-2 4:37 OG-3 4:39	OG-5 4:51 TMS ON 4:53 OG-4 5:17 SLEW(+) 5:19 SLEW(-) 5:29 OG-6 5:31 OG-3 6:19	OG-5 6:32 TMS ON 6:34 OG-4 7:00 OG-6 7:12 BIT HI 7:44 OG-5 7:46 OG-1 7:58 OG-3 8:00	OG-5 EXE 08:13 TMS ON 08:15 OG-4 EXE 08:41 OG-6 EXE 08:53 BIT HI 09:25 OG-5 EXE 09:27 OG-1 EXE 09:39 OG-3 EXE 09:41 OG-5 EXE 09:51 BIT LOW 09:53 TMS ON 09:55 OG-4 EXE 10:09 BIT LOW 10:21 OG-5 EXE 10:23 OG-6 EXE 10:29	OG-5 EXE 10:47 SIT MED 11:11 BIT LOW 11:43 OG-4 EXE 13:17 BIT LOW 13:29 OG-5 EXE 13:31 OG-4 EXE 16:25 BIT LOW 16:37 OG-5 EXE 16:39 OG-4 EXE 21:05 OG-6 EXE 21:17 BIT LOW 21:21 OG-5 EXE 21:23 OG-4 EXE 22:35 OG-6 EXE 22:47 BIT LOW 23:01 OG-5 EXE 23:03 OG-4 EXE 00:11 OG-6 EXE 00:23 OG-7 EXE 00:45 SLEW 360 00:47 BIT LOW 01:09 OG-5 EXE 01:11 OG-4 EXE 01:49 OG-6 EXE 02:01 BIT LOW 02:21 OG-5 EXE 02:23 OG-3 EXE 02:41
COMMENT	○オ5 Rev. PC CNT1 のアドレスが 1 だけ大きく 7° 弱に 2 分早まってしまいました。 同時に、Rep. および 8 秒前に Rec. が入ったため、S-band は Rep. 信号(空)も送り続けることになってしまいました。過去にもあったケースで運用上特に問題なし。こういう場合は <u>US Real</u> を打って、ということになりました。				
SANGLE	144.0 ~ 144.7	STT-Y TEMP (MAX) / 5.3 °C	MIN. -BAT-V (EOD) A 18.2 B 18.3	V (A 19.2 B 19.1 V)	