

# VSOP PROPOSAL COVER SHEETS

ID :

TR :

SR :

DEADLINE : 17 November, 1995

SEND TO : VSOP SOG, ISAS, 3-1-1 Yoshinodai, Sagamihara, Kanagawa 229, JAPAN

Please read Appendix C of Announcement of Opportunity for details on how to fill in this Cover Sheet.

(1) Date prepared : 25-Oct-1995

(2) Proposal title : SVLBI OBSERVATIONS OF THE QUASAR 3C454.3

(3)	INVESTIGATORS	INSTITUTION
P.I.	I. Pauliny-Toth	MPIfR, Bonn, Germany
co-I.	A. Kemball	NRAO, Socorro, USA
co-I.	P. Diamond	NRAO, Socorro, USA
co-I.		
co-I.		
co-I.		
co-I.		
co-I.		
co-I.		

(4) Principal Investigator (or contact person) details...

Name : A. Kemball

Address : NRAO

:PO Box O

:1003, Lopezville Rd.

:Socorro NM 87801, USA

Internet : akemball@aoc.nrao.edu

Other e-mail :

Fax : +01-505-835-7027

Telephone : +01-835-7330

(5) Proposal Abstract :

The OVV Quasar 3C454.3 has been monitored with ground-based VLBI at wavelengths of 2.8, 3.6 and 6 cm from about 1981. Following radio outbursts, it shows both stationary and superluminal components. Recent 7 mm observations detect the core and the nearest (stationary) component. 2 epochs of VSOP+VLBA+Effelsberg+GB43m observations (of 4 orbits each) are requested at 5 GHz and 22 GHz, in connection with ground-based mm-VLBI. The aim is: spectra and separations of core and components; with full polarization imaging as a secondary objective.

**(6) Proposal Category (indicate all that apply):**

Object type:

☒ AGN, ☐ Masers, ☐ Stellar, ☐ Other :

Experiment type:

☐ Single-observation, ☒ Monitoring, ☒ Polarization,

☒ Time-critical, ☐ Target of Opportunity, ☐ Other : best UV coverage

**(7) VSOP spacecraft observing mode (see Section 3 and Table 5 of the VSOP Proposer's Guide):**

☒ 2 channel x 16 MHz, 2-bit (Standard mode),

☐ 2 channel x 32 MHz, 1-bit,

☐ 1 channel x 32 MHz, 2-bit

Phase calibration tones:

☒ On (Standard continuum mode),

☐ Off (Standard spectral line mode)

(Include justification of any non-standard choice at (14) below)

**(8) Ground radio telescope setup**

Polarization : (see (14) below)

☐ VSOP Standard (IEEE LCP), ☒ Non-standard : RCP & LCP

Recording mode :

☐ As for VSOP spacecraft (Standard), ☒ Other : 4 chan x 16 MHz x 2-bit (see (14))

**(9) Investigator participation in scheduling**

☒ PI (or co-I) wishes to participate in scheduling ground radio telescopes

☒ PI (or co-I) wishes to participate in scheduling the space radio telescope

**(10) Preferred correlator (see Sections 9.11 and 12 of VSOP Proposer's Guide):**

☐ No preference, ☐ Mitaka, ☒ Socorro, ☐ Other :

**(11) Preferred post-correlation data analysis location:**

☐ Home Institution, ☐ Mitaka, ☒ NRAO AOC, ☐ JIVE, ☐ Other

**(12) Post-correlation data analysis assistance required:**

☐ None, ☒ Consultation, ☐ Extensive help

**(13) Details of proposed experiments**

An 'experiment' is one or more observations of one source in one wavelength band.

A request to observe the same source in all 3 wavelength bands requires 3 columns to be filled in.

To observe the same source at the same frequency multiple times – a 'monitoring experiment' – requires only one column to be filled in.

Number of experiments in this proposal: 2

	Experiment 1	Experiment 2	Experiment 3	Experiment 4
Source name	3C454.3	3C454.3		
RA (hh mm ss.s)	22 51 29.5203	22 51 29.5203		
Dec (dd mm ss)	15 52 54.311	15 52 54.311		
J2000 or B1950?	B1950	B1950		
Observing frequency band (GHz)	22	5		
<i>Continuum observations:</i>				
Standard VSOP freq. channels?	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Channel A range (MHz)				
Channel B range (MHz)				
<i>Spectral line observations:</i>				
Ch.A spectral line rest freq. (MHz)				
Ch.A LSR velocity (km/s)				
Ch.B spectral line rest freq. (MHz)				
Ch.B LSR velocity (km/s)				
Min. spectral channels per IF channel				
Correlator averaging time (sec)				
FWHM of field of view required (mas)				
No. of correlating passes (if >1)				
Measured total flux density (Jy)	11.7	10		
Measured correlated flux density on > 5000 km baseline (Jy)	2.44 @10 <sup>4</sup> km	~ 3		
Image RMS needed (mJy/beam)	0.1	0.1		
<i>Ground Radio Telescopes:</i>				
<i>Preferred choice:</i>				
Number of medium telescopes	10	10		
Number of large telescopes	2	2		
Suggested array given at Item (14)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<i>Minimum acceptable:</i>				
Number of medium telescopes	10	10		
Number of large telescopes	1	1		
Suggested array given at Item (14)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<i>Length of observation:</i>				
Preferred length (orbits)	4	4		
Minimum acceptable length (orbits)	4	4		
<i>Scheduling constraints:</i>				
Preferred P.A. of beam <i>major</i> axis (deg)				
‘No holes’ ( <i>u,v</i> ) coverage?	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<i>Or</i> maximum resolution ( <i>u,v</i> ) coverage?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Preferred range of dates for scheduling (for monitoring experiments give range for 1st observation only)	96-12-15 to 97-01-03	96-12-15 to 97-01-03	to	to
<i>For monitoring programs:</i>				
Number of observations	2	2		
Mean interval (days)	240	240		
Acceptable variance from mean (days)	90	90		

(14) Additional notes to the scheduler :

Exp 1, Pref Array = VLBA, EF, GB, Min. Array = VLBA, EF.

If tape resources are granted for dual polarization recording on the ground array, this need not be a full 256 Mbps mode. The aggregate bit rate could be reduced by preferential recording during periods at which coverage on the ground-space baselines is maximized. Limited observations of standard polarization calibrators would be necessary on the ground array (see (9) above).

An *optional* request for dual polarization recording is being made for the GRT, subject to the availability of tape resources. If not granted the standard VSOP and GRT mode is implied in (8) above.

NB.: Excellent uv-coverage is obtained in December 96 to early Jan 97, given the proposed orbit. The first observations for this strong and peculiar source should start then! Given this orbit, such conditions do not recur till mid-1998!

- (15) Attach a scientific and technical justification, not in excess of 2 pages of text and 2 pages of figures. Up to one page of  $(u,v)$  plots per source may optionally be included.  
(Refer to the VSOP Announcement of Opportunity for detailed instructions.)  
Preprints and reprints will not be forwarded to the Scientific Review Committee.

Send two paper copies of the complete proposal to:

VSOP Observing Proposals  
VSOP Science Operations Group  
Institute of Space and Astronautical Science  
3-1-1 Yoshinodai, Sagami-hara  
Kanagawa 229 JAPAN

In addition, e-mail the completed L<sup>A</sup>T<sub>E</sub>X file to [submit@vsopgw.isaslan1.isas.ac.jp](mailto:submit@vsopgw.isaslan1.isas.ac.jp)

Cover Sheets of accepted proposals will be made available to the astronomical community.

**Proposals must be received at ISAS by 17 November 1995**